

# Visqueen Gas Barrier Jointing System

- A comprehensive system for ensuring integrity of Visqueen Gas Barrier laps and joins.
- Visqueen Double Sided Jointing Tape for sealing laps.
- Visqueen Foil Backed Girth Jointing Tape for added security.
- Visqueen Top Hat Units where Visqueen Gas Barrier is punctured by service pipes.

## Description

### Visqueen Gas Barrier Jointing System

Visqueen Gas Barrier Jointing Tape is a double sided butyl based jointing tape. The use of a single release paper assists ease of application on site. Visqueen Gas Barrier Jointing Tape is suitable for use in the lapping and sealing of Visqueen Gas Barrier. **All laps of Visqueen Gas Barrier must be a minimum of 150mm and bonded using Visqueen Gas Barrier Jointing Tape. The joint should be secured with Visqueen Foil Backed Girth Jointing Tape.** This tape is a single sided tape which provides added security against any potential leakage path. Always ensure that the membrane is clean and dry at the time of installation.

	Visqueen Double Sided Jointing Tape	Visqueen Foil Backed Girth Jointing Tape
Roll Length (m)	10	50
Roll Width (mm)	50	75

### Visqueen Top Hat Units

Visqueen Top Hat Units are available in various sizes, the most common being 110mm diameter. Visqueen Top Hat Units should be used to form airtight seals around service entry points. The base of the Top Hat Unit should be sealed to Visqueen Gas Barrier using **Visqueen Gas Barrier Jointing Tape** and **Visqueen Foil Backed Girth Jointing Tape**. The unit should be fastened to the service pipe using a combination of **Visqueen Gas Barrier Jointing Tape** and a jubilee clip system to provide fastness.

### Technical Advice

For advice on detailing or installation call Visqueen Building Products Technical Help Line 01993 779911.

### Pricing & Availability

Prices may be obtained from our UK Network of merchant stockists. For details of these call our Sales Office on 01993 776346

The information given in this brochure is based on data and knowledge correct at the time of printing. Statements made in this brochure are of a general nature and are not intended to apply to any use or application outside any referred to in the literature. As conditions of usage and installation are beyond our control we do not warrant performance obtained but strongly recommend that our installation guidelines and the relevant British Standard Codes of Practice are adhered to. Please contact us if you are in any doubt as to the suitability of application.